

## OPTICAL THICKNESS GAUGE

## 157/137 Series



### Non-contact thickness measurement of transparent and semi-transparent materials.

Bristol Instruments offers a family of instruments that employ proven optical technology to provide the most precise and reliable thickness measurement available. Hard and soft materials as thin as 12  $\mu\text{m}$  and as thick as 80 mm can be measured with an unprecedented level of accuracy, versatility, and convenience. What's more, these systems measure thickness in real-time, making them ideal for integration into a production process to improve yields, reduce costs, and increase quality.

### Typical Applications:

- **Optical Components and Lens Assemblies:**  
Measures individual components and multi-element stacks
- **Glass Slimming:**  
Provides real-time multi-point measurements
- **OLED, AMOLED, and LCD Displays:**  
Simultaneously measures total and individual layer thickness, including laminating adhesives
- **Contact and Intraocular Lenses:**  
Simultaneously measures center thickness and sagittal height
- **Medical Balloon Catheters:**  
Measures wall thickness of body, neck, and cone
- **Medical Tubing:**  
Simultaneously measures wall thickness, outer diameter, and inner diameter

### Features:

- Measures hard and soft materials without damage or deformation.
- Compatible with materials ranging from 12  $\mu\text{m}$  to 80 mm.
- All layers (including air gaps) are measured simultaneously.
- Accuracy as high as  $\pm 0.1 \mu\text{m}$ .
- Long-term measurement repeatability up to  $\pm 0.02 \mu\text{m}$ .
- Continuous calibration with a built-in standard of length.
- Traceable to NIST standards.
- Configurations available to allow for up to eight test stations with one instrument.
- Several interfacing options to enable convenient integration.
- Rugged design for manufacturing environments.
- Three-year warranty covers all parts and labor.

**CONTACT US TO SCHEDULE A  
FREE ANALYSIS OF YOUR PART.**

Send us your part and we will provide a live video demonstration of our measurement capabilities.

# SPECIFICATIONS

**157/137 Series**

| MODEL                                                                                                                                                                                                             | 157                                            | 157LS                        | 157XLS                       | 137       | 137LS | 137XLS |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------|------------------------------|------------------------------|-----------|-------|--------|
| <b>THICKNESS MEASUREMENT</b>                                                                                                                                                                                      |                                                |                              |                              |           |       |        |
| Method                                                                                                                                                                                                            | Non-contact optical interferometry             |                              |                              |           |       |        |
| Maximum Physical Thickness<br>(Layer of air with index of refraction of 1.0)                                                                                                                                      | 12 mm                                          | 40 mm                        | 80 mm                        | 12 mm     | 40 mm | 80 mm  |
| Maximum Physical Thickness<br>(Material with index of refraction of 1.5)                                                                                                                                          | 8 mm                                           | 26 mm                        | 53 mm                        | 8 mm      | 26 mm | 53 mm  |
| Minimum Physical Thickness <sup>1</sup><br>(Material with index of refraction of 1.5)                                                                                                                             | 16 μm                                          | 20 μm                        | 24 μm                        | 35 μm     |       |        |
|                                                                                                                                                                                                                   | 12 μm<br>(± 1.0 μm accuracy)                   | 12 μm<br>(± 1.0 μm accuracy) | 16 μm<br>(± 1.0 μm accuracy) |           |       |        |
| Accuracy <sup>2</sup>                                                                                                                                                                                             | ± 0.1 μm                                       |                              |                              | ± 1.0 μm  |       |        |
| Repeatability <sup>3,4</sup>                                                                                                                                                                                      | ± 0.02 μm                                      |                              |                              | ± 0.05 μm |       |        |
| Traceability                                                                                                                                                                                                      | Verified with NIST certified gauge blocks      |                              |                              |           |       |        |
| Units                                                                                                                                                                                                             | mm, μm, mils                                   |                              |                              |           |       |        |
| <b>MEASUREMENT RATE</b>                                                                                                                                                                                           |                                                |                              |                              |           |       |        |
|                                                                                                                                                                                                                   | 20 Hz                                          | 7 Hz                         | 4 Hz                         | 20 Hz     | 7 Hz  | 4 Hz   |
| <b>INSTRUMENT INTERFACE</b>                                                                                                                                                                                       |                                                |                              |                              |           |       |        |
| USB and Ethernet with Windows-based display program<br>Ethernet can be used for network connection allowing instrument access to up to 8 clients<br>Library of commands for LabVIEW, .NET, and custom programming |                                                |                              |                              |           |       |        |
| <b>COMPUTER REQUIREMENTS <sup>5</sup></b>                                                                                                                                                                         |                                                |                              |                              |           |       |        |
| PC running Windows 10, 1 GB available RAM, USB 2.0 (or later) port, monitor, pointing device                                                                                                                      |                                                |                              |                              |           |       |        |
| <b>OPTICAL SWITCH <sup>6</sup></b>                                                                                                                                                                                |                                                |                              |                              |           |       |        |
| Capacity                                                                                                                                                                                                          | Integrated 1 x 8 fiber switch                  |                              |                              |           |       |        |
| Switch Time <sup>7</sup>                                                                                                                                                                                          | 1 ms                                           |                              |                              |           |       |        |
| <b>ENVIRONMENTAL <sup>8</sup></b>                                                                                                                                                                                 |                                                |                              |                              |           |       |        |
| Warm-Up Time                                                                                                                                                                                                      | None                                           |                              |                              |           |       |        |
| Temperature                                                                                                                                                                                                       | 15°C to +30°C (-10°C to +70°C storage)         |                              |                              |           |       |        |
| Pressure                                                                                                                                                                                                          | 500 – 900 mm Hg                                |                              |                              |           |       |        |
| Humidity                                                                                                                                                                                                          | ≤ 90% R.H. at + 40°C (no condensation)         |                              |                              |           |       |        |
| <b>DIMENSIONS AND WEIGHT</b>                                                                                                                                                                                      |                                                |                              |                              |           |       |        |
| Dimensions (H x W x D)                                                                                                                                                                                            | 3.5" x 17.0" x 15.0" (89 mm x 432 mm x 381 mm) |                              |                              |           |       |        |
| Weight                                                                                                                                                                                                            | 17 lbs ( 7.65 kg)                              |                              |                              |           |       |        |
| <b>POWER REQUIREMENTS</b>                                                                                                                                                                                         |                                                |                              |                              |           |       |        |
| 90 - 264 VAC, 47 - 63 Hz, 80 VA max                                                                                                                                                                               |                                                |                              |                              |           |       |        |
| <b>WARRANTY</b>                                                                                                                                                                                                   |                                                |                              |                              |           |       |        |
| 3 Years (parts and labor)                                                                                                                                                                                         |                                                |                              |                              |           |       |        |

- (1) Measurements can be made down to 12 μm (157, 157LS) and 16 μm (157XLS), but with lower accuracy.
- (2) Defined as measurement uncertainty, or maximum thickness error, with a confidence level of ≥ 99.7%. Accuracy is verified with NIST Traceable gauge blocks up to 50mm.
- (3) Standard deviation for a 60 minute measurement period.
- (4) Specification is given for 1 mm sample with an index of refraction of 1.5. Dependent on the reflectivity of the material under test at the probe wavelength of 1.3 μm. Specification is given at 4% reflectivity. When reflectivity is lower, repeatability is reduced to a worst case of about ± 0.15 μm.
- (5) Required for initial optical probe alignment and use with the Windows-based display program. Not required for measurement.
- (6) Integrated fiber optic switch included with models 157-8, 157LS-8, 157XLS-8, 137-8, 137LS-8 and 137XLS-8.
- (7) Switch time has no effect on system's measurement rate.
- (8) Characteristic performance, but non-warranted.

Bristol Instruments reserves the right to change the specifications as may be required to permit improvements in the design of its products. Specifications are subject to change without notice.

